



SEAKING



PO BOX 1
BANKSTOWN
NSW 2200
AUSTRALIA

W www.ausmarine.biz
F +61 2 9772 4857
F +61 2 9772 4858

It's time to change your world and get out on the water with the all-new range of Seaking 2 and 4 stroke outboard motors that bring fun within your reach.

2-Stroke



SPECS:

MODELS:	OTH9.9	OTH15	OTH30	OTH40
Max. Output	9.9HP/7.3KW	15HP/11.00KW	30HP/22.05KW	40HP/29.4KW
Full Throttle Operating Range	4500-5500rpm	4500-5500rpm	4500-5500rpm	4500-5500rpm
Stroke	2	2	2	2
Cylinder	2	2	2	2
Displacement	246mL	246mL	703mL	703mL
Bore X Stroke	56*50mm	56*50mm	80*70mm	80*70mm
Length X Width X Height	873*332*1040mm	873*332*1040mm	1073*402*1350mm	1073*402*1350mm
Weight	36kg	36kg	73.6kg	73.6kg
Gear Ratio	2.08(27:13)	2.08(27:13)	2(26:13)	2(26:13)
Gear Shift Position	F-N-R	F-N-R	F-N-R	F-N-R
Ignition System	CDI	CDI	CDI	CDI
Cooling System	Water-cooling	Water-cooling	Water-cooling	Water-cooling
Starting System	Manual	Manual	Manual/Electric	Manual/Electric
Control System	Tiller control	Tiller control	Tiller control/Remote control	Tiller control/Remote control
Lubrication System	Mixed fuel & oil	Mixed fuel & oil	Mixed fuel & oil	Mixed fuel & oil
Capacity Of Fuel Tank	24L	24L	24L	24L
Recommended Oil	Regular lead-free gasoline	Regular lead-free gasoline	Regular lead-free gasoline	Regular lead-free gasoline
Recommended Lubricant	2 stroke outboard engine lubricant	2 stroke outboard engine lubricant	2 stroke outboard engine lubricant	2 stroke outboard engine lubricant
Recommended Gear Oil	Hypoid gear oil-SAE#90	Hypoid gear oil-SAE#90	Hypoid gear oil-SAE#90	Hypoid gear oil-SAE#90
Recommended Propeller	J	J	3*12-1/4"4*8"~3*11-1/4"14".	3*12-1/4"4*8"~3*11-1/4"14".

* Propeller choice will vary by boat size and application.

4-Stroke



SeaKing
efficient powerful silent clean

SPECS:

MODELS:	F2.5	F4/F5	F6	F8	F9.9	F15
Max. Output	1.8KW	2.9KW	4.4KW	5.8KW	7.3KW	11KW
Full Throttle Operating Range	5250-5750	4000-5000	4000-5000	4500-5500	4000-5000	4500-5500
Stroke	4	4	4	4	4	4
Cylinder	1	1	2	2	2	2
Displacement	72	112	197	197	323	323
Bore X Stroke	54*31.5	59*41	56*40	56*40	59*59	59*59
Length X Width X Height	623*345*1021	S:717*361*1029 L:717*361*1156	S:927*350*998 L:927*350*1125	S:927*350*998 L:927*350*1125	S:1000*427*1080 L:1000*427*1207	S:1000*427*1080 L:1000*427*1207
Weight	17	S:22 L:23	S:37 L:38.5	S:37 L:38.5	S:45 L:47	S:45 L:47
Gear Ratio	2.08(27/13)	2.08(27/13)	2.08(27/13)	2.08(27/13)	2.93(38/13)	2.08(27/13)
Gear Shift Position	F-N	F-N-R	F-N-R	F-N-R	F-N-R	F-N-R
Ignition System	TCI	TCI	CDI	CDI	CDI	CDI
Cooling System	Water-cooling	Water-cooling	Water-cooling	Water-cooling	Water-cooling	Water-cooling
Starting System	Manual	Manual	Manual	Manual	Manual/Electric	Manual/Electric
Control System	Tiller control	Tiller control	Tiller control	Tiller control	Tiller control /Romete control	Tiller control /Romete control
Capacity Of Fuel Tank	0.9	1.1	12-24	12-24	12-24	12-24
Recommended Oil	Regular lead -free gasoline	Regular lead -free gasoline	Regular lead -free gasoline	Regular lead -free gasoline	Regular lead -free gasoline	Regular lead -free gasoline

SeaKing outboard motors are **Efficient** and low on fuel consumption without compromising performance. They are renowned for their endurance and reliability, making them your ideal partner for life on the waterways.

Powerful and responsive, SeaKing motors deliver smooth and effortless performance every time you twist the throttle. Big on power and hungry for work, they never tire of the task, and their advanced technology ensures optimum performance whatever the load.

SeaKing outboards are impressively **Silent** at any speed and virtually silent at low rpm's as they deliver access to the world of boating pleasure and adventure you've been waiting for.



PO BOX 1
BANKSTOWN
NSW 2200
AUSTRALIA

W www.ausmarine.biz
P +61 2 9772 4857
F +61 2 9772 4858

Call us on 9772 4857 or visit our website on www.ausmarine.biz