



efficient powerful silent clean





PO BOX 70 BANKSTOWN NSW 2200 AUSTRALIA

w www.ausmarine.biz

**+**61 2 9772 4857 **F** +61 2 9772 4858

It's time to change your world and get out on the water with the all-new range of SeaKing 2 and 4 stroke outboard motors that bring fun within your reach.

## 2-Strokes



## SPECS:

MODELS:	OTH9.9	OTH15	OTH30	OTH40	
Max. Output	9.9HP/7.3KW	15HP/11.00KW	30HP/22.05KW	40HP/29.4KW	
Full Throttle Operating Range	4500-5500rpm	4500-5500rpm	4500-5500rpm	4500-5500rpm	
Stroke	2	2	2	2	
Cylinder	2	2	2	2	
Displacement	246mL	246mL	703mL	703mL	
Bore X Stroke	56*50mm	56*50mm	80*70mm	80*70mm	
Length X Width X Height	873*332*1040mm	873*332*1040mm	1073*402*1350mm	1073*402*1350mm	
Weight	36kg	36kg	73.6kg	73.6kg	
Gear Ratio	2.08(27:13)	2.08(27:13)	2(26:13)	2(26:13)	
Gear Shift Position	F-N-R	F-N-R	F-N-R	F-N-R	
lgnition System	CDI	CDI	CDI	CDI	
Cooling System	Water-cooling	Water-cooling	Water-cooling	Water-cooling	
Starting System	Manual	Manual	Manual/Electric	Manual/Electric	
Control System	Tiller control	Tiller control	Tiller control/Remote control	Tiller control/Remote control	
Lubrication System	Mixed fuel & oil				
Capacity Of Fuel Tank	24L	24L	24L	24L	
Recommended Oil	Regular lead-free gasoline	Regular lead-free gasoline	Regular lead-free gasoline	Regular lead-free gasoline	
Recommended Lubricant	2 stroke outboard engine lubricant	2 stroke outboard engine lubricant	2 stroke outboard engine lubricant	2 stroke outboard engine lubricant	
Recommended Gear Oil	Hypoid gear oil-SAE#90	Hypoid gear oil-SAE#90	Hypoid gear oil-SAE#90	Hypoid gear oil-SAE#90	
Recommended Propeller	J	J	3*12-1/4"4*8"~3*11-1/4"*14".	3*12-1/4"4*8"~3*11-1/4"*14".	

## **4-Strokes**





## SPECS:

MODELS:	F2.5	F4/F5	F6	F8	F9.9	F15
Max. Output	1.8KW	2.9KW	4.4KW	5.8KW	7.3KW	11KW
Full Throttle Operating Range	5250-5750	4000-5000	4000-5000	4500-5500	4000-5000	4500-5500
Stroke	4	4	4	4	4	4
Cylinder	1	1	2	2	2	2
Displacement	72	112	197	197	323	323
Bore X Stroke	54*31.5	59*41	56*40	56*40	59*59	59*59
Length X Width X Height	623*345*1021	S:717*361*1029 L:717*361*1156	S:927*350*998 L:927*350*1125	S:927*350*998 L:927*350*1125	S:1000*427*1080 L:1000*427*1207	S:1000*427*1080 L:1000*427*1207
Weight	17	S:22 L:23	S:37 L:38.5	S:37 L:38.5	S:45 L:47	S:45 L:47
Gear Ratio	2.08(27/13)	2.08(27/13)	2.08(27/13)	2.08(27/13)	2.93(38/13)	2.08(27/13)
Gear Shift Position	F-N	F-N-R	F-N-R	F-N-R	F-N-R	F-N-R
lgnition System	TCI	TCI	CDI	CDI	CDI	CDI
Cooling System	Water-cooling	Water-cooling	Water-cooling	Water-cooling	Water-cooling	Water-cooling
Starting System	Manual	Manual	Manual	Manual	Manual/Electric	Manual/Electric
Control System	Tiller control	Tiller control	Tiller control	Tiller control	Tiller control /Romete control	Tiller control /Romete control
Capacity Of Fuel Tank	0.9	1.1	12-24	12-24	12-24	12-24
Recommended Oil	Regular lead -free gasoline	Regular lead -free gasoline	Regular lead -free gasoline	Regular lead -free gasoline	Regular lead -free gasoline	Regular lead -free gasoline

SeaKing outboard motors are *Efficient* and low on fuel consumption without compromising performance. They are renowned for their endurance and reliability, making them your ideal partner for life on the waterways.

**Powerful** and responsive, SeaKing motors deliver smooth and effortless performance every time you twist the throttle. Big on power and hungry for work, they never tire of the task, and their advanced technology ensures optimum performance whatever the load.

SeaKing outboards are impressively *Silent* at any speed and virtually silent at low rpm's as they deliver access to the world of boating pleasure and adventure you've been waiting for.



PO BOX 70 BANKSTOWN NSW 2200 AUSTRALIA

w www.ausmarine.biz

+61 2 9772 4857 F +61 2 9772 4858